

## MAXICHARGER DC FAST

### DC Charger

Experience the future of electric vehicle charging with the MaxiCharger DC Fast. This powerful charger redefines fast charging, providing unparalleled efficiency and reliability for EV owners and operators.

#### DC Output Connection

Charging Mode	Mode 4: CCS2
Output Power	60kW/120kW/180kW/240kW
Output Voltage	CCS2: Standard: 200A; Optional 300A (Nominal), 400A (Peak) CHAdeMO: 125A or 200A
Number of Outputs	2*CCS2, or 1*CCS2+1*CHAdeMO; 1*AC socket (Optional)
Peak Efficiency	≥96%



#### AC Input Connection

Earthing System	3P, N, PE
Input Voltage	3-phase 400V AC f10%
Input Frequency	50Hz
Power Factor	≥0.99
Harmonic distortion (THDi)	≥5%

#### General Characteristics

IP and IK Rating	IP54; IK10
Operating Altitude	2000m
Operating Temperature Range	-35°C~+55°C
Storage Temperature Range	-40°C~+70°C
Mounting	Floor Standing
Dimensions (H x W x D)	1950h820h600mm (60kW/120kW) 1950h820h700mm (180kW/240kW)
Screen Type	27 inch LCD Touch Screen (1920*1080)
Cable Length	4m standard; 5m, 6.5m or 7m optional

#### User Interface

Status Indication	LED/LCD/APP
User Interface	Autel Charge APP Autel Charge Cloud
Connectivity	4G, Wi-Fi, Ethernet
Communication Protocols	OCPP 1.6J (Can be Upgraded to OCPP 2.0.1 Later)
User Authentication	APP, RFID Card, Credit card (Optional)

#### Certification and Specifications

Safety and Compliance	IEC 61851-23 IEC 61851-21-2 ISO 15118
Certification	CE, EMC Class A, Eichrechtskonform (Optional)
Warranty	24 months Warranty Extension Possible

#### Software Update

Software Update	OTA Updates via Web Portal
-----------------	----------------------------

# EUNICE

Eunice Energy Group  
Chimarras 5, 15125, Marousi, Attica, Greece  
Tel.: +30 210 3242020, Fax: +30 210 3242023  
Production Unit: Evnikis 10, 19600, Mandra, Attica, Greece  
[info@eunice-group.com](mailto:info@eunice-group.com)  
[www.eunice-group.com](http://www.eunice-group.com)